

PVD Series Split Flow Piston Pump



Features

- **Compact**
Easy installation in the engine room due to very short overall length.
- **Less Than 1% Flow Difference**
Flow difference between each port is minimum.
- **High Efficiency**
Axial piston pump can maintain high efficiency at high pressure ranges.
- **Total Horsepower Control - The Engine Will Never Stall**
The constant horsepower control, including feedback from option gear pump, can keep the pump drive power under the engine power curve.
- **Optional Gear Pump**
Single or double gear pumps can be installed on the back of piston pump.
- **Eliminate Piping for the Case Drain**

Specifications

Model	Max. displacement	Max. pressure	Drive speed			Constant torque control	Option G: Gear pump P: Power shift B: Valve block	Mass
			Max. speed	Rated speed	Min. speed			
	cm ³ /rev (in ³ /rev)	MPa (psi)	min. ⁻¹	min. ⁻¹	min. ⁻¹	kg (lbs)		
PVD-00B	8x2 (0.49x2)	24.5 (3553)	2800	2800	900	Standard	G, P (Option)	9 (20)
PVD-0B	12x2 (0.73x2)		2800	2600			G, P, B (Option)	13 (29)
PVD-1B	17x2 (1.04x2)		2700	2500			G, P, B (Option)	15 (33)
PVD-2B	22.5x2 (1.37x2)		2600	2400			G, P, B (Option)	20 (44)
PVD-3B	33x2 (2.01x2)		2400	2200			G, P, B (Option)	27 (60)

NACHI

NACHI AMERICA INC.

17500 23 Mile Road, Macomb, MI 48044

Tel. (800)622-4410 Fax. (586)226-5289

Direct: (312)371-5879

Email: hydraulics@nachi-america.com

www.nachi-hydraulics.com